

# Designed for Efficiency, Delivered in Quality

PRO-560S

PRO-540S

8 colour

 PRO-540S Max. Print Width	 PRO-560S Max. Print Width	 LUCIA PRO ink	 FINE 1.28" Wide Print Head	 L-COA PRO
 Multifunction Roll System	 320 GB Hard Drive	 3.5" Colour LCD Touch Panel	 WiFi Connectivity	 Direct USB Drive Printing



## Professional Production Print Quality

The imagePROGRAF PRO-540S and PRO-560S are the best solutions for large format printing productivity, delivering outstanding quality at high speeds and offering exceptional reliability.

# TECHNICAL SPECIFICATIONS

TECHNOLOGY		PRO-540S	PRO-560S
	Printer Type	8 Colour 44"/1118 mm	8 Colour 60"/1524 mm
	Print Technology	Canon Bubblejet on Demand (12 channels integrated Type x 1 print head)	
	Number of Nozzles	18,432 nozzles (1,536 nozzles x 4 colours, 3072 nozzles x 4 colours)* *The four key colours (C, M, Y, MBk) are arranged symmetrically on the print head	
	Maximum Print Resolution	2400 x 1200 dpi	
	Nozzle Pitch	600 dpi x 2 (includes Non-firing nozzle detection and compensation system)	
	Line Accuracy	±0.1% or less User adjustments necessary. Printing environment and media must match those used for the adjustments. CAD paper required: Plain paper, CAD tracing paper, coated paper, CAD translucent matte film only	
	Ink Droplet Size	minimum 4pl per colour	
	Ink Capacity	Sales ink: 160ml/330ml/700ml Bundled starter ink: 330ml (C/M/Y/MBk), 190ml(PC/PM/Bk/GY)	
	Ink Type	Pigment inks - Black, Matte Black, Cyan, Magenta, Yellow, Photo Cyan, Photo Magenta, Grey	
	OS Compatibility	Microsoft Windows 32 Bit: Vista, 7, 8, 8.1, 10, Server 2008, 64 Bit: Vista, 7, 8, 8.1, 10, Server 2008/R2, Server 2012/R2 Apple Macintosh: OSX 10.7.5 ~ 10.11	
MEMORY			
	Standard Memory	3 GB	
	Hard Drive	320 GB	
FIRMWARE			
	Printer Language	SGRaster (Swift Graphic Raster)	
	PDF	Supported Version 1.7 - List of the built-in fonts: Times-Roman, Helvetica, Courier, Symbol, Times-Bold, Helvetica-Bold, Courier-Bold, Zapf Dingbats, Times-Italic, Helvetica-Oblique, Courier-Oblique, Times-Bold Italic, Helvetica-Bold Oblique, Courier-Bold Oblique	
	JPEG	Supported Version JFIF1.02	
	Job Control	IVEC	
	Status Reply	SNMP-MIB (Standard MIB, Canon-MIB), IVEC, CPCA	
	Direct Print	JPEG/PDF	
	Type	Flash ROM	
	Update	Updated from USB, Ethernet port (Utility use)	
OPERATION PANEL			
	Display	LCD (3.5 inch/8.8 cm TFT colour)	
	Language on Operation Panel	16 Languages Selectable: Japanese/English/German/Italian/Spanish/Brazilian Portuguese/Dutch/Polish/Russian/Danish/Simplified Chinese/ Traditional Chinese/Korean/Thai/Indonesian/Turkish	
INTERFACE			
USB A Port	Type	USB Memory (Direct Print)	
USB B Port	Type	Built-in (Hi-Speed USB)	
	Mode	Full Speed (12 Mbit/sec), High Speed (480 Mbit/sec), Bulk transfer	
	Connector type	Series B (4 pins)	
Gigabit Ethernet	Type	Built-in	
	Standard	• IEEE 802.3 10base-T • IEEE 802.3u 100base-TX / Auto-Negotiation • IEEE 802.3ab 1000base-T / Auto-Negotiation • IEEE 802.3x Full Duplex	
	Protocol	SNMP [Canon-MIB, HTTP, TCP/IP (IPv4/IPv6)]	
Wireless LAN	Standard	IEEE802.11n/IEEE802.11g/IEEE802.11b	
	Security	• WEP (64/128bit) • WPA-PSK (TKIP/AES) • WPA2-PSK (TKIP/AES)	
PRINTING SPEED			
MEDIA TYPE	PRINT MODE	A0 SIZE	
Plain Paper <sup>1</sup>	(Level 5)	00:55	
	Fast	01:34	
	Standard	02:51	
Coated Paper <sup>1</sup>	Fast	01:35	
	Standard	02:51	
	High	05:36	
Glossy Photo Paper HG 255 <sup>1</sup>	Fast	02:58	
	Standard	04:46	
	High	05:36	

<sup>1</sup> Print speed is based on the default setting using ISO JIS SCID N5 image and does not take into account data processing time on host computers.  
Print speed may vary depending on the system configuration, interface, software, document complexity, print mode, page coverage, type of paper used, etc.

MEDIA HANDLING		PRO-540S	PRO-560S
Media Feed and Output		Roll Paper: One Roll, Front-loading, Front Output Optional Roll Paper: One Roll, Front-loading, Front Output Cut Sheet: Front-loading, Front Output (Manual feed)	Roll Paper: Two Roll, Front-loading, Front Output Cut Sheet: Front-loading, Front Output (Manual feed)
Media Width		Roll paper: 203.2 mm~1118 mm Cut sheet: 203.2 mm~1118 mm	Roll paper: 203.2 mm~1524 mm Cut sheet: 203.2 mm~1524 mm
Media Thickness		Roll/Cut: 0.07 ~ 0.8 mm	
Minimum Printable Length		203.2 mm	
Maximum Printable Length		Roll paper: 18 m (Varies according to the OS and application) Cut sheet: 1.6 m	
Maximum Media Roll Diameter		170 mm	
Media Core Size		Internal diameter of roll core: 2"/3"	
Margins Recommended Area		Roll paper: Top: 20 mm, Bottom: 3 mm, Side: 3 mm Cut sheet: Top: 20 mm, Bottom: 20 mm, Side: 3 mm	
Margins Printable Area		Roll paper: Top: 3 mm, Bottom: 3 mm, Side: 3 mm Roll paper (borderless): Top: 0 mm, Bottom: 0 mm, Side: 0 mm Cut sheet: Top: 3 mm, Bottom: 20 mm, Side: 3 mm	
Media Feed Capacity		Roll Paper: One roll If second option is added then automatic switching is possible Cut Sheet: 1 sheet	Roll Paper: Two roll automatic switching possible Cut Sheet: 1 sheet
Media Take-Up Roll Unit		Dual direction roll take-up unit	
Borderless Printing Width (Roll Only)		Recommended: 515 mm (JIS B2), 728 mm (JIS B1), 1030 mm (JIS B0), 594 mm (ISO A1), 841 mm (ISO A0), 10", 14", 17", 24", 36", 42", 44", Printable: 257 mm (JIS B4), 297 mm (ISO A3), 329 mm (ISO A3+), 420 mm (ISO A2), 8", 16", 30", 300 mm	Recommended: 515 mm (JIS B2), 728 mm (JIS B1), 1030 mm (JIS B0), 594 mm (ISO A1), 841 mm (ISO A0), 10", 14", 17", 24", 36", 42", 44", 50", 54", 60" Printable: 257 mm (JIS B4), 297 mm (ISO A3), 329 mm (ISO A3+), 420 mm (ISO A2), 8", 16", 30", 300 mm
Maximum Number of Delivered Prints		Standard position: 1 sheet Flat position: A2 landscape, glossy paper less than 10 sheets, Coated paper less than 20 sheets (excludes strong curled condition)	
POWER AND OPERATING REQUIREMENTS			
Power Supply		AC 100-240V (50-60Hz)	
Power Consumption		Operation: 107 W or less Standby: 1.8 W or less Power off: 0.5 W or less	Operation: 113 W or less Standby: 1.8 W or less Power off: 0.5 W or less
Operating Environment		Temperature: 15~30°C, Humidity: 10~80% RH (no dew condensation)	
Acoustic Noise (Power/Pressure)		Operation: 49 dB (A) (Glossy paper, Print priority: Standard) Standby: 35 dB (A) or less Operation: 6.6 Bels or less (Glossy paper, Image, Print priority: Standard) (Measured on ISO7779 standard)	
Environment Certificates		RoHS	
WHAT'S INCLUDED			
What's in the Box?		Printer, 1 x print head, 3" paper core attachment, EU & UK Power Cable, 1 set of starter ink tanks, Set up guide, Safety/Standard Environment leaflet, User software CD-ROM (OSX/Windows), PosterArtist Lite CD-ROM, EU Biocide Sheet, Eurasian Economic Union Sheet, Important Information Sheet, Quick Guide and Printhead Alignment Sheet	
Software Included		imagePROGRAF PRO Printer Driver, Print Plug-In for Office, Quick Utility Toolbox and PosterArtist Lite Other software available as download from web.	
ACCESSORIES OPTIONS			
Printer Stand		Inclusive with printer	
2 <sup>nd</sup> Roll Unit		RU-41	RU-61 (mandatory)
2/3" Roll Holder		RH2-45	RH2-65
CONSUMABLES			
Ink Tank		PFI-51 (160ml), PFI-53 (330ml), PFI-57 (700ml)	
Print Head		PF-10	
Cutter Blade		CT-07	
Maintenance Cartridge		MC-30	
DIMENSIONS & WEIGHT		PRO-540S	PRO-560S
Packaged Dimensions W x D x H (mm) / Weight (kg)	Printer (Main unit with pallet)	1820 x 915 x 1019 mm / Approx. 182 kg	2227 x 915 x 1022 mm / Approx. 211 kg
	Roll Unit	1727 x 562 x 461 mm / Approx. 31 kg	2133 x 562 x 461 mm / Approx. 40 kg
Physical Dimensions W x D x H (mm) / Weight (kg) (including Roll Holder Set, excluding ink and print head)	Main Unit + Stand + Basket	Basket Closed: 1593 x 766 x 1168 mm	Basket Closed: 1999 x 766 x 1168 mm
		Basket Opened: 1593 x 984 x 1168 mm	Basket Opened: 1999 x 984 x 1168 mm
	Main Unit + Roll Unit + Stand + Basket	Approx. 121 kg	Approx. 137 kg
		Basket Closed: 1593 x 766 x 1168 mm	Basket Closed: 1999 x 766 x 1168 mm
		Basket Opened: 1593 x 984 x 1168 mm	Basket Opened: 1999 x 984 x 1168 mm
	Approx. 141 kg	Approx. 163 kg	
			



imagePROGRAF  
PRO-540S | PRO-560S

## Professional Production Print Quality



**Canon**  
Delighting You Always

CANON SINGAPORE PTE. LTD.  
1 Fusionopolis Place, #15-10 Galaxis, Singapore 138522  
Tel : 65-6799-8888 | Fax : 65-6799-8882 | [www.canon-asia.com](http://www.canon-asia.com)

Tel : 65-6799-8888  
Fax : 65-6799-8882  
[www.canon-asia.com](http://www.canon-asia.com)

CANON BUSINESS PARTNER / DEALER'S STAMP

This document is for information purpose only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and product names are trademarks and/or registered trademarks of their respective owners.

Warning: Unauthorised recording of copyrighted materials may infringe on the rights of copyright owners and be contrary to copyright laws.