


# Project the Future Today with Solid-State HLD LED



LH-WU350UST  
(Ultra Short-Throw)



LH-WX370UST  
(Ultra Short-Throw)



With the latest solid-state HLD (High Lumen Density) LED light source, Canon's new line-up of projectors realise high resolution with long-lasting lamp life of up to approx. 20,000 hours<sup>(\*)</sup>. Compared to conventional mercury lamp with an average lifespan of 3,000 hours, the solid-state HLD LED drastically reduces operational cost. Together with a new concentrated light pass system that supports a smaller chassis, the projectors are both lightweight and compact.

## High Brightness Projection

With HLD LED, the LH-SERIES achieves brilliant projection with accurate colour reproduction, making it ideal for meeting rooms, classrooms and conference rooms.

(LH-WU350UST: 3,500lm | LH-WX370UST: 3,700lm)



## Ultra Short-Throw Projection

The LH-WU350UST and LH-WX370UST ultra short-throw projectors are capable of displaying a 80-inch image with a mere projection distance of 41cm, making it excellent for limited spaces such as retail stores and museums.



SPECIFICATIONS

Model		LH-WU350UST	LH-WX370UST
Display system		Transmissive LCD: 3 panels	
Optical system		Three primary colour liquid crystal shutter projection method	
Display device	Effective display area size	0.64"×3 / 16:10	
	Effective number of pixels	2,304,000 (1920x1200) x3	1,024,000 (1280x800) x3
Projection lens	Zoom	Fixed	
	Focus	Manual	
	Focal length	f=2.9 mm	
	F number	F:1.7	
Light source		HLD LED	
Image size/installation distance		80~120 inch / 0.0~18.4 cm	
Number of colours		1,073,000,000 colours	
Light output <sup>(*1)(*2)</sup>		3500 lm	3700 lm
Contrast ratio <sup>(*1)(*2)</sup>		100000:1	
Ratio of brightness at periphery to center <sup>(*1)</sup>		75%	
Speaker		16W (mono), x1	
Displayable scanning frequency	Horizontal	15 kHz~100 kHz	
	Vertical	28 Hz~85 Hz	
Display resolution	Computer signal input	Maximum input resolution 1920x1200 dots	Maximum input resolution 1920x1200 dots (resizing display)1280x800 dots
	Video signal input	NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N	
Other terminals and connectors	Mini D-sub 15-pin	Analog PC (WUXGA/FHD/UXGA/WSXGA+/SXGA+/SXGA/WXGA+/WXGA/XGA/SVGA/VGA/Mac16"), x2 Component video (1080p/1080i/720p/576p/576i/480p/480i)	
	HDMI x2	Digital PC (WUXGA/FHD/UXGA/WSXGA+/SXGA+/SXGA/WXGA+/WXGA/XGA/SVGA/VGA/Mac16") Digital video (1080p/1080i/720p/576p/576i/480p/480i)	
	RCA	Video input	
	RJ-45	Network connection (100 Base-TX (100Mbps) / 10 Base-T (10Mbps), Network display)	
	USB Type B	USB connection (USB display, service port)	
	USB Type A	USB connection (Memory viewer), Power supply (Max1.5A)	
	Dsub-9	RS-232 connection	
	Mini D-sub 15-pin	Analog video output	
	Mini jack x2	Audio input x1, Audio output x1	
	2RCA	Audio input	
Noise (Normal/Eco <sup>(*3)</sup> )		39/33dB	
Operating temperature		0°C~40°C	
Power supply		AC 100-240V, 50/60 Hz	
Maximum power consumption (Normal/Eco <sup>(*3)</sup> )		525W / 298W	525W / 295W
Standby mode power consumption (LAN OFF/ON)		0.4W / 2W	
Dimensions		(W) 408 mm × (H) 173 mm × (D) 428 mm (including protrusion) (W) 408 mm × (H) 169 mm × (D) 428 mm (not including protrusion)	
Weight		Approx. 10kg	
Accessories included		Remote control, dry-cell batteries for remote control, power cord, computer cable and important information	

\*1 Lamp: Normal, Image mode: Presentation  
\*2 Compliance with ISO21118-2012  
\*3 Eco mode: 20,000 hours (Eco value is based on estimated calculation and is not guaranteed as specification)

This document is for information only and the contents are subject to change without notice. Errors and omissions excepted. Images are simulated. Weight and dimensions are approximates. Nothing in this document should be construed as warranty. Insist on an original warranty from your sales companies. Product/ Service options, name and availability may vary by region. We expressly disclaim any liability or contractual obligations with respect to this document. Canon, among others are trademarks of Canon Inc. and/or its affiliates. Other names, marks and logos contained in this document may be registered trademarks or trademarks of their respective owners.



SOUTH & SOUTHEAST ASIA  
REGIONAL HEADQUARTERS

CANON SINGAPORE PTE. LTD.  
1 Fusionopolis Place,  
#15-10 Galaxis,  
Singapore 138522

<https://asia.canon>

0220W251

CANON OFFICES

**HONG KONG**  
Canon Hongkong Company Limited  
Tel : 852-3191 2388  
Fax : 852-2369 3800  
<https://hk.canon>

**MALAYSIA**  
Canon Marketing (Malaysia) Sdn Bhd  
Tel : 60-3-7844 6000  
Fax : 60-3-7845 0505  
<https://my.canon>

**PHILIPPINES**  
Canon Marketing (Philippines), Inc.  
Tel : 632-884-9090  
Fax : 632-556-1456  
<https://ph.canon>

**SINGAPORE**  
Canon Singapore Pte. Ltd.  
Tel : 65-6799-8888  
Fax : 65-6799-8882  
<https://sg.canon>

**THAILAND**  
Canon Marketing (Thailand) Co. Ltd  
Tel : 66-2-344 9999  
Fax : 66-2-344 9960  
<https://th.canon>

**VIETNAM**  
Canon Marketing (Vietnam) Co. Ltd  
Tel : 84-8-3820 0466  
Fax : 84-8-3820 0477  
<https://vn.canon>

CANON BUSINESS PARTNERS

**BANGLADESH**  
J.A.N. Associates Ltd.  
Tel : 880-2 9660 601  
Fax : 880-2 8610 410  
[www.jan-bd.com](http://www.jan-bd.com)

**BRUNEI**  
Interhouse Company  
Tel : 673-2-653-001  
Fax : 673-2-653-003  
[www.ihc.com.bn](http://www.ihc.com.bn)

**CAMBODIA**  
i-Click Marketing Co., Ltd.  
Tel : 855-23-996638  
Fax : 855-23-996639  
[www.i-click.com](http://www.i-click.com)

**INDONESIA**  
PT. Datascip  
Tel : 62-21-6544515  
Fax : 62-21-6544811-13  
<https://id.canon>

**MALDIVES**  
SIMDI Company Pvt. Ltd.  
Tel : 960 333 4421  
Fax : 960 333 4424  
<http://www.simdi.com/simdi-technology>

**MONGOLIA**  
ITZone LLC  
Tel : 976-7731-7731  
[www.itzone.mn/en](http://www.itzone.mn/en)

**MYANMAR**  
Myanmar Golden Rock  
International Co., Ltd.  
Tel : 95-1 654810  
to 19 (10 Lines)  
Fax : 95-1 654820  
[mgr.com.mm](http://mgr.com.mm)

**NEPAL**  
International Electronics Concern  
(P) Ltd  
Tel : 977-1-442 1991  
Fax : 977-1-442 1909  
[www.iec.com.np](http://www.iec.com.np)

**PAKISTAN**  
Shirazi Trading Company (Pvt.) Ltd.  
Tel : 92-21-38704830-41  
Fax : 92-21-35170860  
<https://stc.atlas.pk>

**SRI LANKA**  
Metropolitan Photohub (Pvt) Ltd  
Tel : 94 11-4700 200  
Fax : 94 11-4700 398  
[www.metropolitan.lk](http://www.metropolitan.lk)