

imageRUNNER
C3226i

Canon
Delighting You Always

THE POWER OF EFFICIENCY

REFINING THE WORKFLOW

Intuitive and incredibly functional, the new imageRUNNER C3226i refines routine workflow to amplify efficiency.



Touch Panel



Print/Copy/Scan/Fax



Mobile Support



Wi-Fi
Connectivity



Optimal Security

Business Can Be Simple

imageRUNNER C3226i

MAKING ROUTINE TASKS A BREEZE

Streamline routine tasks with the functional and capable new imageRUNNER C3226i. The new multi-function device is packed with features that can cater to individual's workflows so users can stay productive and efficient with simplified operations

EASY NAVIGATION, GREAT USABILITY

The user-friendly 7-inch colour touch panel display ensures excellent visibility, offering clear and easy browsing through touch operations such as "flick" and "drag-and-drop".



GREATER MEDIA SUPPORT

Print with the preferred media type at any point in time. The imageRUNNER C3226i can be loaded with a wide range of paper types and sizes for specific tasks, supporting your various paper needs.



MEDIA TYPE & SIZE



Letterhead



Up to 300gsm



SRA3 to
A6R



Pre-Punched
Paper

CONVENIENT PRINT OUTPUTS

The new imageRUNNER C3226i has various finishing options, such as ECO-Staple, Staple-On-Demand and hole punching. This reduces manual collating after output, so your documents are instantly ready and in the right configuration.





FLEXIBLE CONNECTIVITY

Mobile support and printing can be quick and easy. With the QR code feature, scan and connect your mobile devices directly via the Canon PRINT Business application. Preview and print documents on the go by connecting directly to the multi-function device.



YOU CAN DOWNLOAD FROM
APP STORE OR GOOGLE PLAY

RETHINK SECURITY

The latest security features comes as standard on the new imageRUNNER C3226i, increasing the safety of your documents and for better gate-keeping.



UNIFLOW ONLINE/ ONLINE EXPRESS



uniFLOW Online/Online Express enables personal authentication before documents are printed, reducing lost printouts and erroneous transmissions.

DOCUMENT PROTECTION



Printouts can be held with Force Hold Print until verification is performed at the machine, preventing information leakage from documents left unattended at the machine.

DEVICE PROTECTION



Prevent unauthorised modifications through Verify System at Startup which checks the integrity of the device firmware and applications during startup.

SPECIFICATION

MAIN UNIT	
Machine type	A3 Color Laser Multifunctional
Core functions	Print, Copy, Scan, Send and Optional Fax
Control Panel	7 inch TFT LCD WVGA color Touch panel
Memory	Standard: 2.0GB RAM
Storage	eMMC: 30GB
Interface Connection	Network Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n)
	Others Standard: USB 2.0 (Host) x 2, USB 2.0 (Device) x 1
Paper Supply Capacity (A4, 80gsm)	Standard: 1,200 sheets Maximum: 2,300 sheets (with Cassette Feeding Unit-AW1)
Paper output capacity (A4, 80gsm)	Standard: 250 sheets Maximum: 650 Sheets (with Inner Finisher-L1 and Copy Tray-T1)
Finishing capabilities	Collate, Group, Offset, Staple, Hole Punch, ECO-Staple , Staple-On-Demand *Finishing capabilities vary depending on the options connected.
Supported media types	Multi-purpose Tray: Thin, Plain, Heavy*, Recycled, Coated, Colour, Tracing, Bond, Transparency, Label, Pre-punched, Letterhead, Envelope *SRA3 is unsupported for Coated (257-300gsm) and Heavy(257-300gsm) paper.
	Upper / Lower Cassette Thin, Plain, Recycled, Colour, Heavy, Bond, Transparency, Pre-punched, Letterhead, Envelope* * Envelope Feeder Attachment Kit (standard) is required.
Supported media sizes	Multi-purpose tray: Standard size: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R Custom size: 98.4 x 139.7 mm to 320.0 x 457.2 mm Envelopes: COM10 No.10, Monarch, ISO-C5, DL Envelope custom size: 98.0 x 98.0 mm to 320.0 x 457.2 mm
	Upper Cassette: Standard size: A4, A5, A5R, A6R, B5 Custom Size: 105.0 x 148.0 mm to 297.0 x 215.9 mm Envelope: ISO-C5 *Envelope Feeder Attachment Kit B (standard) is required.
Supported media weights	Lower Cassette: Standard size: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R Custom Size: 105.0 x 148.0 mm to 304.8 x 457.2 mm Envelopes*: COM10 No.10, Monarch, DL *Envelope Attachment Kit A (standard) is required.
	Multi-purpose tray: 52 to 300 gsm Upper/Lower Cassette: 52 to 256 gsm Duplex: 52 to 220 gsm
Warm-up Time (Quick start mode: ON)	4 Seconds or Less* * Time from device power on to when copy icon appears and is enabled to operate on the touch panel display.
	From Sleep Mode: 10 seconds or less 10 Seconds or Less* *Time from device power on, until copy ready (not print reservation)
Dimensions (W x D x H)	565 x 687 x 891 mm
Installation Space (W x D)	1,168 x 1,116 mm
Weight	Approx. 76.9 kg including toner (with DADF-BA1)
PRINT SPECIFICATIONS	
Print Speed (BW/CL)	1-sided: Up to 26/26 ppm (A4, A5, A5R, A6R), Up to 20/20 ppm (A4R), Up to 15/15 ppm (A3)
	2-sided: Up to 13/13 ppm (A4, A5R), Up to 10/10 ppm (A4R), Up to 7/7 ppm (A3)
Print Resolution (dpi)	600 x 600 1,200 x 1,200 (half-speed)
Page description languages	Standard: UFR II, PCL6 Optional: Adobe® PostScript®3™
Direct Print	Supported file types: RUI: PDF, EPS, TIFF/JPEG, XPS USB Memory: PDF, TIFF/JPEG, XPS Network Place: PDF, TIFF/JPEG, XPS
Printing from mobile and cloud application	AirPrint, Mopria, Canon PRINT Business, uniFLOW Online and Universal Print
Fonts	PS fonts: 136 Roman PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T* ¹ (Japanese, Korean, Simplified and Traditional Chinese) , Barcode fonts* ²
	*1 Requires optional PCL INTERNATIONAL FONT SET-A1 *2 Requires optional BARCODE PRT KIT-D1
Operating System	UFR II: Windows® 8.1/10/Server 2012/Server 2012 R2/Server 2016/Server 2019, MAC OS X (10.11 or later)
	PCL: Windows® 8.1/10/Server 2012/Server 2012 R2/Server 2016/Server 2019 PS: Windows® 8.1/10/Server 2012/Server 2012 R2/Server 2016/Server 2019, MAC OS X (10.11 or later) PPD: Windows® 8.1/10, MAC OS X (10.11 or later)
COPY SPECIFICATIONS	
Copy Speed (BW/CL)	1-sided: Up to 26/26 ppm (A4, A5, A5R, A6R), Up to 20/20 ppm (A4R), Up to 15/15 ppm (A3) 2-sided : Up to 13/13 ppm (A4, A5R), Up to 10/10 ppm (A4R), Up to 7/7 ppm (A3)
First-Copy-Out Time (A4) (BW)	Approx. 7.0 / 8.7 seconds or less
Copy resolution (dpi)	600 x 600
Multiple Copies	Up to 999 copies
Copy Density	Automatic or Manual (9 Levels)
Magnification	25% - 400% (1% Increments) Preset reduction/enlargement: 25%, 50%, 61%, 70%, 81%, 86%, 100%, 115%, 122%, 141%, 200%, 400%

SCAN SPECIFICATIONS	
Type	Optional: DADF-BA1 [2-sided to 2-sided] or Platen Cover-Y3 DADF: Duplexing Automatic Document Feeder
Document Feeder Paper Capacity (80 gsm)	Up to 100sheets
Acceptable originals and weights	Platen: Sheet, Book and 3-Dimensional objects
	Document Feeder media weight: 1-sided scanning: 30 to 128 gsm (BW), 64 to 128 gsm (CL) 2-sided scanning: 50 to 128 gsm (BW), 64 to 128 gsm (CL) Platen: max. scanning size: 297.0 x 431.8 mm
Supported media sizes	Document Feeder media size: A3, A4, A4R, A5, A5R, B4, B5, B5R, B6 Custom size: 128.0 x 139.7 mm to 297.0 x 431.8 mm
Scan Speed (ipm: BW/CL; A4)	DADF: 1-sided Scanning: 70/70 (300 dpi, send), 51/42 (600 dpi, copy) 2-sided Scanning: 35/35 (300 dpi, send), 25.5/25.5 (600 dpi, copy)
	Scan for Copy: Up to 600 x 600 Scan for Send : (Push, BW) up to 600 x 600, (Pull, BW) up to 600 x 600 (Push, CL) up to 300 x 300, (Pull, CL) up to 300 x 300 Scan for Fax : Up to 600 x 600
Scan Resolution (dpi)	
Pull Scan Specifications	Color Network ScanGear2. For both TWAIN and WIA
Supported OS	Windows® 8.1/ 10/ Server2012/ Server2012 R2/ Server 2016/ Server 2019
SEND SPECIFICATIONS	
Destination	Standard: E-mail/Internet FAX (SMTP), SMB3.0, FTP, WebDAV Optional: Super G3 FAX
Address Book	LDAP (2,000)/ Local (1,600) /One-touch (200)
Send resolution (dpi)	Push: 100 x 100, 150 x 150, 200 x 100 (Normal), 200 x 200 (Fine), 200 x 400* (SuperFine), 300 x 300, 400 x 400* (UltraFine), 600 x 600 *
	Pull: 75 x 75, 100 x 100, 150 x 150, 200 x 200, 300 x 300, 400 x 400*, 600 x 600* *Only applicable for black and white, even if colour mode is selected.
Communication protocol	File: FTP (TCP/IP), SMB3.0 (TCP/IP), WebDAV Email/iFax: SMTP (send), POP3 (receive)
File Format	Standard: TIFF (MMR), JPEG*, PDF (Compact, Searchable, PDF/A-1b, Encrypted), XPS (Compact, Searchable), PDF/XPS (Device Signature), Office Open XML (PowerPoint, Word)
	Optional: PDF (Trace & Smooth), PDF/XPS (User Signature) *Single page only
STORE SPECIFICATIONS	
Memory Media	Standard: USB Memory
FAX SPECIFICATIONS	
Maximum Number of Connection Lines	1
Modem Speed	Super G3: 33.6 kbps G3: 14.4 kbps
Compression Method	MH, MR, MMR, JBIG
Resolution (dpi)	400 x 400 (Ultrafine), 200 x 400 (Superfine), 200 x 200 (Fine), 200 x 100 (Normal) Sending: A3, A4, A4R, A5 ¹ , A5R ¹ , B4, B5 ² , B5R ¹ Receiving: A3, A4, A4R, A5R, B4, B5, B5R
Sending/Receiving Size	*1 Sent as A4 *2 Sent as B4 short
FAX memory	Up to 30,000 pages
Speed dials	Max. 200
Group dials/destinations	Max. 199 dials
Sequential broadcast	Max. 256 addresses
Memory backup	Yes
ENVIRONMENTAL SPECIFICATIONS	
Operating Environment	Temperature: 10 to 30 °C Humidity: 20 to 80% RH (Relative Humidity)
Power source	220-240V 50/60Hz 4A
Power consumption	Maximum: Approx. 1,500 W Standby: Approx. 44 W ¹ Sleep mode: Approx. 2 W ² , Approx. 1 W ³
	*1 Reference value: measured one unit *2 Wireless LAN power save mode OFF *3 Wireless LAN power save mode ON *2*3 Sleep mode is not available in all circumstances due to certain settings.
CONSUMABLES	
Toner Yield (Estimated @ 5% Coverage)	NPG-67 TONER BK: 36,000 pages NPG-67 TONER C/M/Y: 19,000 pages NPG-67L TONER C/M/Y: 2,500 pages
PAPER SUPPLY OPTIONS	
Cassette Feeding Unit-AW1	Paper Capacity: 550 sheets x 2 (1,100 sheets) (80 gsm) Paper Type: Thin, Plain, Recycled, Colour, Heavy, Bond, Transparency, Pre-punched, Letterhead Paper Size: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, Custom Size: 105.0 x 148.0 mm to 304.8 x 457.2 mm Paper Weight: 52 to 256 gsm Power Source: From the Main Unit Dimensions (W x D x H): 565 x 635 x 248 mm Weight: Approx. 16.0 kg
OTHER ACCESSORIES	
Platen Cover-Y3,DADF-BA1, Utility Tray-B1, Option Attachment kit for Reader-A2, Inner 2way Tray-M1, Copy Tray-T1, Inner Finisher-L1, Inner 2/3 Hole Puncher-D1, Inner 2/4 Hole Puncher-D1, Copy Card Reader Attachment-H3, IC Card Reader Attachment-B3,Copy Card Reader-F1, PCL International Font Set-A1,PCL Asian Font Set-A1,PS Printer Kit-CS1, Universal Send Trace & Smooth PDF Kit-A1,Universal Send Digital User Signature Kit-C1,Barcode Printing Kit-D1,Copy Control Interface Kit-D1,Super G3 FAX Board-BJ1, Remote Fax Kit-A1,ADF Access Handle-A1, Media Adjustment kit-A1, Staple-P1	



SOUTH & SOUTHEAST ASIA REGIONAL HEADQUARTERS

CANON SINGAPORE PTE. LTD.

1 Fusionpolis Place #14-10 Galaxis, Singapore 138522

Tel: 65-6799-8888 | Fax: 65-6799-8882 | <https://asia.canon>